

The logo for AVstart features the letters 'AV' in a bold, red, sans-serif font. A white swoosh underline is positioned beneath the 'A' and 'V'. To the right of 'AV', the word 'start' is written in a bold, black, italicized sans-serif font.

AVstart

High technology make beautiful life



Yoosee Series Indoor Camera

PJ202



PJ202



Specifications

Model	PJ202
Main processor	AK3918EV300
Image sensor	1/2.9" CMOS F37
Lens	3.6mm 1080P HD lens
View Angle	Horizontal 60° , Vertical 38°
Night vision	Dual Filter, IR-Cut, 9pcs IR Leds
Pan / Tilt	Pan: 355° , Tilt: 90°
Video compression	H.265 Dual Stream
Resolution	2MP (Max 20fps)
Audio compression	AAC/G.711, Two-way Intercom
Network interface	1*RJ45 10M/100M Adaptive Ethernet port
Wi Fi & Frequency	IEEE802.11 a/b/g/n; Frequency: 2.4~ 2.4835GHz
Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
APP	Yoosee
Protocols	Private Protocol
Socket	1* Micro SD Card Slot, Support Up to 128G
Alarm Notification	APP Message
Alarm Mode	Motion detection
Power Supply	DC5V / 2A
Power Consumption	< 5W
Working Condition	Temperature:-10°C~+50°C, Humidity 10%~ 95%



Yoosee Series Outdoor PTZ Camera

QA201H/QAB202



AVstart HD WiFi CAMERA

1920*1080 | Two-way Audio | 24GHz Network
24/7 Live View | Motion Detection | Infrared Night Vision
FTP Storage | Micro SD Card Storage up to 128G
Looping Record | IP66 Waterproof

QA201H/QAB202



Specifications	
Model	QA201H/QAB202
Main processor	Realtek3903/AK3918EV300
Image sensor	1/2.8" CMOS Starlight SC2239/1/2.9" CMOS F37
Lens	3.6mm 1080P HD lens
View Angle	Horizontal 60° , Vertical 38°
Night vision	12pcs IR Leds/8pcs IR Leds
Pan / Tilt	Pan: 355° , Tilt: 90°
Video compression	H.264 Dual Stream
Resolution	2MP (Max 20fps)
Audio compression	AAC/G.711, Two-way Intercom
Network interface	1*RJ45 10M/100M Adaptive Ethernet port
Wi Fi & Frequency	IEEE802.11 a/b/g/n; Frequency: 2.4~ 2.4835GHz
Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
APP	Input: built-in microphone; output: built-in speaker
Protocols	Private Protocol
Socket	1* Micro SD Card Slot, Support Up to 128G
Alarm Notification	APP Message
Alarm Mode	Motion detection
Material	Plastic
Power Consumption	< 5W
Working Condition	Temperature:-10°C~+50°C, Humidity 10%~ 95%



Baby monitor Series

BABY MONITOR BEST BABY CARE



Lullabies



Night Vision



Feeding
Reminder



Wireless
Connection



Temperature
Alarm



PTZ Camera



Two -Way Audio



Sound
Detection

BM101



Specifications	
Model	BM101
Compression	H.265
Screen size	5" inch HD LCD
Lens	3.6mm 1080P HD lens
View Angle	Horizontal 60° , Vertical 38°
Night vision	9pcs IR Leds
Pan / Tilt	Pan: 355° , Tilt: 90°
Wireless Technology:	2.4 GHz FHSS
Resolution	1MP
Baby unit rechargeable battery	rechargeable
Lullabies	play 5 lullabies
Possibility of additional cameras	max can add 4 camera
Battery autonomy	4 hours
Reach distance Range (up to)	300m
Socket	1* Micro SD Card Slot, Support Up to 128G
Material	Plastic
Power Consumption	< 5W
Working Condition	Temperature:-10°C~+50°C, Humidity 10%~ 95%

The logo for AVstart features the letters 'AV' in a bold, red, sans-serif font. A white swoosh underline is positioned beneath the 'A' and 'V'. To the right of 'AV', the word 'start' is written in a bold, black, italicized sans-serif font.

AVstart

High technology make beautiful life